

Surface Preparation Vacuums & Separators

DuoVac

Electric, 220Volt, Concrete Dust Vacuum, 680 cfm

- Two vacuums combined to produce 680 CFM and 100 H₂O
- Vacuum-On-Demand - control suction with individual motor control switch gear.
- Great for grinders up to 44" and four-7" hand grinders
- Use included common distribution box to power grinder with the vacuums
- Foot lever actuated dustpan or use with Ruwac 12" HEC separation system
- Dust free emptying
- Quick disconnect cart needs no tools for assembly
- Carbon impregnated, compression cast composite modular housing



Motor Type:	Three Phase	Vacuum Pressure:	100 (H ₂ O)"
Voltage:	230 Volt 3 phase	Air Movement	680 CFM
Amp:	30 Amp	Filter Area	56 ft ² MicroClean
Distribution Box:	230 Volt 3 phase 60 amp	HEPA:	Optional 80 ft ²
Shaker:	Manual	Inlet:	3" Heavy-Duty Double
Collection Capacity	18 gal	Caster:	2.75"
Dimensions:	32 x 20 x 51	Weight:	169 lbs

HEC: High Efficiency Cyclone

Eliminate down time and frequent filter changes with Ruwac's HEC cyclones and collect up to 97% of the debris prior to reaching the filters.

- 10-gauge powder coated cyclone lid
- Rubberized internal drop out chamber
- 10-gauge drum dolly with 3" casters
- "H" bracket swivel cart connector
- Grounded vacuum hose.
- Vacuum to cyclone lid
- Tipping cart assembly

Cyclone Diameter:	14"
CFM Range:	375-525
Inlet:	4"
Capacity:	30 gallons
Lid Diameter:	19.75"
Height:	68"
Weight:	34 lbs



Distributed by:



54 Winter St.
 Holyoke, MA 01040
 413.532.4030
 ConcreteVacuums.com
 info@Ruwac.com

